

CME CRUMBLERS PRODUCT SPECIFICATIONS







MILL-CRM 639

CRUMBLER 5HP

MILL-CRM 660 CRUMBLER 10HP

Motor	10 HP, 1750 RPM, 208-230/460V
Roll Dimensions	60" L x 6" W
Flanged Infeed Dimensions	58" L x 18.5" W
Flanged Outfeed Dimensions	58" L x 18.5" W
Total Dimensions	76" L x 40" W x 22" H
Capacity / HR	6-10 TONS

MILL-CRM 624 CRUMBLER 3HP

3 HP, 1750 RPM, 208-230/460V	5 HP, 1750 RPM, 208-230/460V
24" L x 6" W	39" L x 6" W
24" L x 5" W	40" L x 5" W
24" L x 18.5" W	39" L x 18.5" W
40" L x 40" W x 22" H	76" L x 40" W x 22" H
1 – 4 TONS	4 - 6 TONS

CME engineers crumblers for simplicity, featuring triangleshaped serrations on rolls, spring-loaded pressure, builtin bypass, and a low-profile design.

Common applications include: Poultry Feed, Aquatic Feed, Bedding, and Fertilizer Pellets.

TECHNICAL ADVANTAGES

- Easy to maintain belt-drive design
- 9 corrugations per inch
- ▶ Adjustable roll gap for varying particle sizes
- ▶ Low profile construction for compact installation
- ► Full-length hinged maintenance door for roll inspection and clean-up
- Designed with a bypass option
- Designed, assembled, & supported in the USA
- ▶ CME's Signature 1-Year Manufacturer's Warranty

OPTIONS

- Single Phase Motor
- ▶ Safety Motor Starter

COMMON MATERIALS

- Alfalfa
- Corn
- General Feed
- ► Hemp/Cannabis
- Oats

- Poultry Litter
- Soybean Meal
- Wheat
- Wood
- Fertilizer

COMMON INDUSTRIES

- Fertilizer
- Animal Feed
- ▶ Hemp/Cannabis
- Wood Processing



Our equipment is engineered in the USA and supported in the USA

Lifetime Engineering, Technical & Application Support